










COB DOWNLIGHT

Model No.	Picture	Price (Excl GST)	Product description			
AT-DLC22-3-13W 3inch		Triac dim \$40.89 0-10V dim Add \$6.00 Dali dim Add \$8.00 IP44 Add \$2.50	Power 13W Voltage 100-240V / 200-240V Beam angle 60° LED COB CCT 2700/3000K/4000K/5000K CRI > 80 Lumens 850-950lm	Dimension Ø110X70mm cutout90-100mm Withstand voltage AC3750V Driver Isolated driver efficiency≥86% IP: 20 / 44 Materials Die-casting aluminium+ Glass Certificate CE (EMC LVD ErP RoHS) SAA Packing 41*30*59 30PCS 18.5KGS		
AT-DLC22-4-18W 4inch		Triac dim \$61.50 0-10V dim Add \$4.00 Dali dim Add \$7.00 IP44 +USD1.5	Power 18W Voltage 100-240V / 200-240V Beam angle 60° LED COB CCT 2700/3000K/4000K/5000K CRI > 80 Lumens 1250-1350lm	Dimension Ø145X80mm cutout 120-130mm Withstand voltage AC3750V Driver Isolated driver efficiency≥86% IP: 20 / 44 Materials Die-casting + PMMA Certificate CE (EMC LVD ErP RoHS) SAA Packing 37*35*61 20PCS 18KGS		
AT-DLC22-4-25W 4inch		Triac dim \$63.81 0-10V dim Add \$11.00 Dali dim Add \$8.00 IP44 Add \$2.50	Power 25W Voltage 100-240V / 200-240V Beam angle 60° LED COB CCT 2700/3000K/4000K/5000K CRI > 80 Lumens 1800-1900lm	Dimension Ø145X80mm cutout 120-130mm Withstand voltage AC3750V Driver Isolated driver efficiency≥86% IP: 20 / 44 Materials Die-casting aluminium+ Glass Certificate CE (EMC LVD ErP RoHS) SAA Packing 37*35*61 20PCS 18KGS		
AT-DLC22-6-18W 6inch		Triac dim \$75.53 0-10V dim Add \$6.00 Dali dim Add \$8.00 IP44 Add \$2.50	Power 18W Voltage 100-240V / 200-240V Beam angle 36°60° LED COB CCT 2700/3000K/4000K/5000K CRI > 80 Lumens 1250-1350lm	Dimension Ø190X90mm cutout 160-170mm Withstand voltage AC3750V Driver Isolated driver efficiency≥86% IP: 20 / 44 Materials Die-casting aluminium+ Glass Certificate CE (EMC LVD ErP RoHS) SAA Packing 68*48*29 12PCS 18KGS		
AT-DLC22-6-25W 6inch		Triac dim \$80.78 0-10V dim Add \$11.00 Dali dim Add \$8.00 IP44 Add \$2.50	Power 25W Voltage 100-240V / 200-240V Beam angle 36°60° LED COB CCT 2700/3000K/4000K/5000K CRI > 80 Lumens 1800-1900lm	Dimension Ø190X90mm cutout160-170mm Withstand voltage AC3750V Driver Isolated driver efficiency≥86% IP: 20 / 44 Materials Die-casting aluminium+ Glass Certificate CE (EMC LVD ErP RoHS) SAA Packing 68*48*29 12PCS 18KGS		
AT-DLC22-6-35W 6inch		Triac dim \$91.29 0-10V dim Add \$13.00 Dali dim Add \$11.00 IP44 Add \$2.50	Power 35W Voltage 100-240V / 200-240V Beam angle 36°60° LED COB CCT 2700/3000K/4000K/5000K CRI > 80 Lumens 2500-2650lm	Dimension Ø190X90mm cutout 160-170mm Withstand voltage AC3750V Driver Isolated driver efficiency≥86% IP: 20 / 44 Materials Die-casting aluminium+ Glass Certificate CE (EMC LVD ErP RoHS) SAA Packing 68*48*29 12PCS 18KGS		
AT-DLC22-8-18W 8inch		Triac dim \$87.94 0-10V dim Add \$6.00 Dali dim Add \$8.00 IP44 Add \$2.50	Power 18W Voltage 100-240V / 200-240V Beam angle 24°60° LED COB CCT 2700/3000K/4000K/5000K CRI > 80 Lumens 1250-1350lm	Dimension Ø225X87mm cutout 200-210mm Withstand voltage AC3750V Driver Isolated driver efficiency≥86% IP: 20 / 44 Materials Die-casting aluminium+ Glass Certificate CE (EMC LVD ErP RoHS) SAA Packing 79*55*47 12PCS 20KGS		
AT-DLC22-8-25W 8inch		Triac dim \$93.19 0-10V dim Add \$13.00 Dali dim Add \$11.00 IP44 Add \$2.50	Power 25W Voltage 100-240V / 200-240V Beam angle 24°60° LED COB CCT 2700/3000K/4000K/5000K CRI > 80 Lumens 1800-1900lm	Dimension Ø225X87mm cutout 200-210mm Withstand voltage AC3750V Driver Isolated driver efficiency≥86% IP: 20 / 44 Materials Die-casting aluminium+ Glass Certificate CE (EMC LVD ErP RoHS) SAA Packing 79*55*47 12PCS 20KGS		
AT-DLC22-8-35W 8inch		Triac dim \$103.70 0-10V dim Add \$13.00 Dali dim Add \$11.00 IP44 Add \$2.50	Power 35W Voltage 100-240V / 200-240V Beam angle 24°60° LED COB CCT 2700/3000K/4000K/5000K CRI > 80 Lumens 2500-2650lm	Dimension Ø225X87mm cutout 200-210mm Withstand voltage AC3750V Driver Isolated driver efficiency≥86% IP: 20 / 44 Materials Die-casting aluminium+ Glass Certificate CE (EMC LVD ErP RoHS) SAA Packing 79*55*47 12PCS 20KGS		

Minimum order quantities apply. 10-20% Surcharge on quantities below MOQ.

Importers and Wholesale Suppliers